



ACME MANUFACTURING CORP.
6532 TOWER LANE, CLAREMORE, OK. 74019

ENGINEERED PRODUCTS BY CRAFTSMEN

Self-Flashing Curb Type SFWNBB (With Wood Nailer & Burglar Bars)

STANDARD FEATURES

Constructed of 18 ga. galv. steel with continuous welded seams and integral base plate for water tightness and extra strength.

Wide base flashing to insure adequate bond to roofing surface for water-tight seal to roof.

Lined with 1½" fiberglass fire proof sound attenuating thermal insulation.



2 x 2 wood nailer secured to top ledge of curb.

Steel ½" bars, 8" on center.

OPTIONS

- Interior metal liner.
- Standard heights of 12, 14, 16, 18, 20, 24", or any special height.
- ¾" bars; any special bar spacing.
- Gasket in lieu of nailer
- Damper shelf – standard or custom size opening.
- Wide flange (6" or 8" wide).
- Back draft damper.
- Damper motor, 120, 240, or 480 vac.
- Protective or decorative coatings.
- Heavy-gage construction.

PROJECT	
LOCATION	
ARCHITECT	
ENGINEER	
CONTRACTOR	
SUBMITTED BY	
DATE	PO#



SPECIFICATIONS AND DIMENSIONS

REFERENCE	QUAN.	MAT'L	L	W	M	H	OPTIONS